

# 东莞市捷森电子有限公司

DONGGUAN J. S ELECTRONICS CO., LTD

Fixed inductors for surface mounting



## ENR3015S SERIES

### FEATURES/特点

- Excellent solderability and high heat resistance.
- Suitable for large currents.
- Is applicable to a wide range of DC-DC converters ideal For (DVD;DSC;phone; PDA;GPS;CMMB; Digital photo, Frame, telephone; CAR AV equipment and so on.)
- Current Rating: Based on the largest decline in ICP to 35 percent, and the temperature does not exceed 40degrees.
- Measuring frequency: 100KHz/0.25V

DIMENSIONS(mm) 外型尺寸

LAND PATTERNS(mm) 焊盘尺寸



Type 型号	Indicate 表示	Inductance 电感量 (μH)	D. C. R (Max) 直流电阻 (mΩ)	Saturation Current 饱和电流 (A)
ENR3015S-1R0N	1R0	1.0μH±30%	40.5	2.10
ENR3015S-1R5N	1R5	1.5μH±30%	48	1.80
ENR3015S-2R2M	2R2	2.2μH±20%	72	1.48
ENR3015S-3R3M	3R3	3.3μH±20%	96	1.20
ENR3015S-4R7M	4R7	4.7μH±20%	144	1.00
ENR3015S-6R8M	6R8	6.8μH±20%	190	0.87
ENR3015S-100M	100	10μH±20%	275	0.70
ENR3015S-150M	150	15μH±20%	430	0.56
ENR3015S-220M	220	22μH±20%	620	0.47
ENR3015S-330M	330	33μH±20%	1000	0.39
ENR3015S-470M	470	47μH±20%	1600	0.32

- Design according to customer requirements.
- Data recorded for reference only, all to provide samples of business shall prevail.
- Recorded content may be improved or changed without notice.