

东莞市捷森电子有限公司

DONGGUAN J. S ELECTRONICS CO., LTD



Fixed inductors for surface mounting
EDRH129 SERIES

FEATURES/特点

- Excellent solderability and high heat resistance.
- Suitable for large currents.
- Is applicable to a wide range of DC-DC converters ideal For (DVD;DSC;phone; PDA;GPS;CMMB; Digital photo, Frame, telephone; CAR AV equipment and so on.)
- Current Rating: Based on the largest decline in ICP to 35 percent, and the temperature does not exceed 40degrees.
- Measuring frequency: 100KHz/0.25V

DIMENSIONS(mm) 外型尺寸

LAND PATTERNS(mm) 焊盘尺寸



Type 型号	Indicate 表示	Inductance 电感量 (μH)	D. C. R (Max) 直流电阻 (mΩ)	Rated Current 饱和电流 (A)
EDRH129-1R0N	1R0	1.0μH±30%	5.5	19.9
EDRH129-2R5N	2R5	2.5μH±30%	8.0	12.2
EDRH129-3R5M	3R5	3.5μH±20%	9.7	12.0
EDRH129-4R7M	4R7	4.7μH±20%	11	10.1
EDRH129-5R6M	5R6	5.6μH±20%	12.4	8.56
EDRH129-7R5M	7R5	7.5μH±20%	14	8.48
EDRH129-100M	100	10μH±20%	18	7.12
EDRH129-150M	150	15μH±20%	26	5.84
EDRH129-220M	220	22μH±20%	29	5.12
EDRH129-330M	330	33μH±20%	53	4.25
EDRH129-470M	470	47μH±20%	63	3.6
EDRH129-680M	680	68μH±20%	93	2.76
EDRH129-101M	101	100μH±20%	126	2.31
EDRH129-102M	102	1000μH±20%	1220	0.7
EDRH129-222M	222	2200μH±20%	2580	0.43

- Design according to customer requirements.
- Data recorded for reference only, all to provide samples of business shall prevail.
- Recorded content may be improved or changed without notice.