

东莞市捷森电子有限公司


DONGGUAN J. S ELECTRONICS CO., LTD

Fixed inductors for surface mounting
ENR6020S SERIES


FEATURES/特点

- Excellent solderability and high heat resistance.
- Suitable for large currents.
- Is applicable to a wide range of DC-DC converters ideal For (DVD;DSC;phone; PDA;GPS;CMMB; Digital photo, Frame, telephone; CAR AV equipment and so on.)
- Current Rating: Based on the largest decline in ICP to 35 percent, and the temperature does not exceed 40degrees.
- Measuring frequency: 100KHz/0. 25V

DIMENSIONS(mm) 外型尺寸



LAND PATTERNS(mm) 焊盘尺寸



Type 型号	Indicate 表示	Inductance 电感量 (μH)	D. C. R (Max) 直流电阻 (mΩ)	Saturation Current 饱和电流 (A)
ENR6020S-0R8N	0R8	0. 8μH± 30%	20	5. 50
ENR6020S-1R5N	1R5	1. 5μH± 30%	26	4. 00
ENR6020S-2R2M	2R2	2. 2μH± 20%	34	3. 20
ENR6020S-3R3M	3R3	3. 3μH± 20%	40	2. 80
ENR6020S-4R7M	4R7	4. 7μH± 20%	58	2. 40
ENR6020S-6R8M	6R8	6. 8μH± 20%	85	2. 00
ENR6020S-100M	100	10μH± 20%	125	1. 70
ENR6020S-220M	220	22μH± 20%	290	1. 05

- Design according to customer requirements.
- Data recorded for reference only, all to provide samples of business shall prevail.
- Recorded content may be improved or changed without notice.